

# ÉQUIPMENT



<b>Equipment Name</b>	<ul style="list-style-type: none"><li>• Hammermill</li></ul>
<b>Characteristics</b>	<ol style="list-style-type: none"><li>1. Milling and attrition of forest, residual or inorganic fillers according to different sieving grids</li></ol>
<b>Details</b>	<ol style="list-style-type: none"><li>1. Hammer grinding at 3,600 RPM</li><li>2. Sieving screens from 20 mm to 2 mm<ul style="list-style-type: none"><li>• 55 HP motor and integrated cyclone</li></ul></li></ol>
<b>Usage</b>	<ul style="list-style-type: none"><li>• The Hammermill type hammer mill allows the fractionation of different bio-based or inorganic materials in order to obtain a more uniform particle size at the end of the process. The fan and cyclone separates fines and dust to collect the right material at the bottom of the cyclone.</li></ul>
<b>Technical specifications</b>	<ol style="list-style-type: none"><li>1. Manufacturier : Radviliskis</li><li>2. Type: Hammer Mill 55</li><li>3. Engine: 55 HP</li><li>4. Diameter of the sieves: 72 cm<ul style="list-style-type: none"><li>• Throughput: <math>\pm 500</math> kg/hour (depending on the material)</li></ul></li></ol>
<b>Examples of use</b>	<b>Forest bark shredding</b> <b>Paper and cardboard attrition</b>

Photo





